



TYNKOLIT-SO 332

Primer for silicone plasters

Areas of application: Primer intended for final preparation of groundwork before the application of silicone plasters. Limits and levels absorbency, reinforces the groundwork, facilitates painting and increases paint adhesion to the groundwork.

Product features: Waterproof
Frost-proof
Vapor-permeable
Increases groundwork adhesion
Facilitates plaster application
Regulates groundwork absorbency

Material base:

- Water dispersion of silicone polymer
- Refining agents
- Quartz aggregate
- Titanium white
- Water

Processing:



Conditions for application: Apply in temperatures from +5°C to +25°C, these temperatures refer to air, groundwork and product temperature. Groundwork must be cleared from dust, grease, anti-adhesive solutions, paint residue, mold, algae, moss, etc., free from cracks and saline efflorescence.

Surface: Reinforce absorbent and dusting surfaces with GRUNTOLIT-W 301. Eradicate all expressions of biological aggression on the groundwork using the SEPTOBUD 1008 solution. Repair all cracked and scratched surfaces with the 428 leveling grout or other, suitable for the groundwork type. The grout in the repaired sites must be completely dry and fixed. Cover all surfaces not intended for priming before the primer is applied.

:

Reinforcing layer in the thermal insulation system: without additional priming
Cement-lime plaster: With high absorbency, prime with GRUNTOLIT-W 301
Cement plaster: without additional priming
Gypsum plaster: prime with GRUNTOLIT-W 301 or GRUNTOLIT-SG 302
Plasterboards: prime with GRUNTOLIT-SG 302
Concrete: without additional priming

Preparation: Ready-to-use product. Do not dilute with water or mix with other materials. Mix thoroughly before use.

Processing: Primer; apply with a roller, brush or using spray application. The average drying time is 24 hours.

Notes: When conducting works in adverse weather conditions, use special covers limiting the effects of external factors.

Storage: Maximally 12 months. In dry areas and in non-damaged factory packaging, at temperatures from +5°C to +25°C.

Technical data

Consumption	from 0.2 to 0.3kg/m ²
pH	c.a. 7



TYNKOLIT-SO 332

Primer for silicone plasters

Technical data

Color	white or dyed
Drying time	c.a. 4h
The possibility of performing further works	after c.a. 24h

General notes:

This sheet supersedes all previous versions. The information included in this technical sheet represents the current knowledge and practical experience. The information sheet contains general information only and shall not be construed as any basis for manufacturer liability for performance and use. Differences and specific execution conditions may occur. The product is to be used according to the required level of technical knowledge and OHS principles. Avoid skin contact and protect the eyes. In the case of eye contact, wash the eyes abundantly with clean water and seek medical assistance. The use of gloves, goggles and protective clothing is recommended.