



MOZATYNK-S 051

Acrylic mosaic render


Areas of application: Mix the ingredients to produce a plaster mortar on the basis of acrylic resin with single-fraction, dyed aggregate
Thin-layer finishing coats for indoor and outdoor applications.
After drying, creates an elastic layer, with good mechanic resistance and permanent color properties.

Product features: Waterproof
Freezeproof
High mechanic durability
Easy to process
UV-resistant

Material base:

- Water dispersion of acrylic polymer
- Dyed quartz aggregate
- Refining agents

Application:



Conditions for application: Apply at temperatures from +5°C to +25°C, these temperature refer to air, groundwork and product temperature. All groundwork surfaces must be load-bearing, tight, stable, even and clean and, if required, primed with GRUNTOLIT-W 301 or GRUNTOLIT-SG 302
Groundwork must be cleared from dust, grease, anti-adhesive solutions, paint residue, mold, algae, moss, etc., free from cracks and saline efflorescence.

Surface: Before applying the plaster, all groundworks must be primed with TYNKOLIT-T 330
Eradicate all expressions of biological aggression on the groundwork using the SEPTOBUD 1008 solution.
Prior to applying TYNKOLIT-T 330, prime very absorbent groundworks with GRUNTOLIT-W 301

Types of substrate:
Cement-lime plaster:
Gypsum plaster:
Reinforcing layer in the thermal insulation system:
Concrete, reinforced concrete:
Plasterboards:

Preparation: The product is ready to use after mixing the ingredients. Do not dilute with water or mix with other materials.
Before applying, check if the color matches your order.

Application: Apply the plaster using a stainless steel long float, and spread the portion to cover the entire groundwork
While performing works and during drying process, the applied plaster shall be protected from frost, rainfalls, too high temperatures and strong winds
It is advisable to use shields on scaffoldings.

Notes: One one surface, apply plaster from one production batch only.
Use properly dyed plastering primer under dyed plasters.
Process a surface in a continuous manner, applying the "wet on wet" method to avoid visible lines.

Storage: Maximally 12 months
In dry areas and in non-damaged factory packaging, at temperatures from +5°C to +25°C.

Technical data

Consumption

fraction 1.8mm - 4.7kg/m²



MOZATYNK-S 051

Acrylic mosaic render

Technical data

Granulation	1,8mm
Drying time	from 12 to 48 hours

General notes:

This product data sheet replaces all its previous versions. The information, included in this technical card, represents our current knowledge and practical experience. This is general information only which shall not obligate the manufacturer to take any responsibility either for workmanship or for the manner of use. For there may be differences and specific execution conditions. The product shall be applied in accordance with required technical knowledge and OHS rules. Avoid contact with skin and protect eyes. In case of contact with eyes, rinse them up with a large quantity of clean water and consult a doctor. It shall be recommended to use gloves, safety goggles and protective clothing.