



# SUPER WHITE PAINT 012 ACRYLIC

<b>Areas of application:</b>	Paint on the basis of water dispersion of acrylic resin, intended for painting interiors. Snow-white
<b>Product features:</b>	Waterproof High whiteness level Efficient Environmentally friendly Indoor use
<b>Material base:</b>	<ul style="list-style-type: none"> <li>• Water dispersion of acrylic polymer</li> <li>• Mineral fillers</li> <li>• Refining agents</li> <li>• Water</li> </ul>
<b>Processing:</b>	
<b>Conditions for application:</b>	Apply in temperatures from +5°C to +25°C, these temperature refer to air, groundwork and product temperature. All groundwork surfaces must be load-bearing, tight, stable, even and clean. Groundwork must be cleared from dust, grease, anti-adhesive solutions, paint residue, mold, algae, moss, etc., free from cracks and saline efflorescence.
<b>Surface:</b>	Depending on the absorbency and type of groundwork, prime with GRUNTOLIT-W 301 or GRUNTOLIT-SG 302 Eradicate all expressions of biological aggression on the groundwork using the SEPTOBUD 1008 solution. Repair all surface irregularities, cracks or cavities with material matching the groundwork. The mortar used in the repair sites must be dry and properly set.
<b>:</b>	<p><b>Cement-lime plaster:</b> Prime with GRUNTOLIT-W 301</p> <p><b>Gypsum plaster:</b> prime with GRUNTOLIT-SG 302</p> <p><b>Plasterboards:</b> prime with GRUNTOLIT-SG 302</p> <p><b>Concrete, reinforced concrete:</b> Pime with GRUNTOLIT-W 301 or EXPERT 6</p> <p><b>Finishing coats:</b> prime with GRUNTOLIT-SG 302</p>
<b>Preparation:</b>	Ready-to-use product. Do not dilute with water or mix with other materials. Mix thoroughly before use. Before applying, check if the color matches your order.
<b>Processing:</b>	Apply the paint with a roller, brush or using a spray-application unit Drying time in optimal conditions is minimum 2 hours
<b>Notes:</b>	Ventilate the rooms during the execution of works, but protect the plaster against drafts causing excessive drying of the surface Paint in a continuous manner on one surface, do not allow any parts of the painted surface to dry out in the process to avoid visible lines Use paint from one production batch on one surface Apply the next layer after a minimum of 6 hours of drying of the previous layer Adverse conditions (high humidity, low temperature) can considerably extend the drying time.
<b>Storage:</b>	Maximally 12 months In dry areas and in non-damaged factory packaging, at temperatures from +5°C to +25°C.

## Technical data

### Consumption

from 0.10 l/m<sup>2</sup> per layer

# SUPER WHITE PAINT 012 ACRYLIC



## Technical data

<b>Density</b>	c.a. 1.45 g/cm <sup>3</sup>
<b>Coat resistance to dry-scrubbing</b>	resistant (no traces on the fabric)
<b>Quality coating</b>	level III

## General notes:

This sheet supersedes all previous versions. The information included in this technical sheet represents the current knowledge and practical experience. The information sheet contains general information only and shall not be construed as any basis for manufacturer liability for performance and use. Differences and specific execution conditions may occur. The product is to be used according to the required level of technical knowledge and OHS principles. Avoid skin contact and protect the eyes. In the case of eye contact, wash the eyes abundantly with clean water and seek medical assistance. The use of gloves, goggles and protective clothing is recommended.